

CLAIMS

5 1. A device for vibration control in a machine for
cutting, said machine comprising a cutting tool supported
by a tool holder, the device comprising a control unit
and converting means which are connectible to the control
unit and comprise a vibration sensor and an actuator, and
the actuator comprising an active element, which converts
10 an A.C. voltage supplied by the control unit to the
actuator into dimensional changes, wherein said active
element is adapted to be embedded in the body of the tool
holder, and wherein said active element is adapted to be
embedded in such manner that said dimensional changes
15 impart turning moments to the body of the tool holder.

2. A device as claimed in claim 1, wherein said
active element is adapted to be embedded with its centre
axis spaced from the centre axis of the tool holder.

3. A device as claimed in claim 1, wherein said
20 active element is adapted to be embedded close to the
surface of the tool holder.

4. A device as claimed in claim 1, said tool holder
being elongated and having an end portion which is
adapted to be received in a mounting recess of the
25 machine, wherein said active element is positioned along
the tool holder such that, when the tool holder is held
in said recess, a portion of said active element is
within said recess.

5. A device as claimed in claim 4, wherein said
30 portion of said active element consists of approximately
half of said active element.

6. A device as claimed claim 1, wherein said active
element is plate-shaped.

7. A device as claimed in claim 1, wherein said
35 actuator comprises a double element which consists of two
active elements which are attached to each other.

T.O. 210-8232360

Sub
A2

Sub B1

Sub B1

Sub⁵
Bb

Qabli

20
Sub
7/11

QubB1

30

35

15. A tool holder as claimed in claim 11, said tool holder being arranged to be mounted in a machine for boring, said tool holder being elongated and having an end portion which is adapted to be received in a mounting recess of the machine, wherein said active element is positioned along the tool holder such that, when the tool holder is held in said recess, a portion of said active element is within said recess.

16. A device as claimed in claim 15, wherein said portion of said active element consists of approximately half of said active element.

17. A tool holder as claimed in claim 11, wherein said active element is arranged in a recess in the tool holder and is connected with the tool holder via a glue joint which transfers at least part of said dimensional change to the tool holder, and that the recess is sealed.

18. A tool holder as claimed in claim 11, wherein said active element is arranged in a recess in the tool holder and has two opposite power transmitting surfaces, said power transmitting surfaces being engaged with surfaces of the body of the tool holder and said dimensional changes changing the distance between the power transmitting surfaces, and that the recess is sealed.

19. A tool holder as claimed in claim 11, the tool holder consisting of an insert holder for a turning lathe.

20. A tool holder as claimed in claim 11, the tool holder consisting of a teeth holder for a milling machine, wherein the teeth holder comprises active elements, which are helically arranged round the centre axis of the teeth holder.

21. A tool holder as claimed in claim 11, the tool holder consisting of a teeth holder for a drilling machine, wherein the teeth holder comprises active elements which are helically arranged round the centre axis of the teeth holder.

FOU240-62232560

Sub
A31

Sub B1

Sub
C31

Sub B1

22. A tool holder as claimed in claim 11, the tool holder comprising an embedded, piezoelectric sensor element.

23. A tool holder as claimed in claim 11, wherein
5 said embedded elements are cast into the body of the tool holder.

24. A tool holder as claimed in claim 11, wherein said active element is a piezoceramic element.

25. Use of a device as claimed in claim 1 in a
10 machine, the machine being one of a machine for turning, a machine for milling or a machine for drilling.

Sub B1

TOUCH SCREEN